

# Shop Order

# Hackney Emergency Vehicle

**Quote For:**

Genesee County  
Emergency Management Services  
15 Main Street  
Batavia, NY 14020

**Ship To:**

Genesee County Emergency Management  
Services Office  
7690 State Street Road  
Batavia, New York 14020

**Exp. Date:** 07/25/2003  
**Quote No:** E1203-0001

**CHASSIS:** VA-40-BE                      BIG EASY  
**BODY:** DFC1173RC                      11-COMP'T RESCUE W/RECESSED ROOF - CUST

10/24/2003

Page 1

PART NO	S	DESCRIPTION	QTY
00-VA-10	S	ADVANTAGE W/ 10" Raised Roof-Flat Floor	1
00-XX-10		Chassis Warranty, One (1) Year	1
00-XX-20		Cab Perforation Warranty, Ten (10) Years	1
01-10-10		Single Rail High Strength Frame	1
01-10-40		Frame Paint, Standard Black	1
01-19-BE		Wheelbase 195"	1
02-10-05		> Fuel tank, 50 Gallon	1
03-10-24		> Front Bumper with 24" extension	1
03-25-20		Tow Hooks, Painted	1
03-30-BE		> (2) Air horns, Grover, CENTER BEHIND BUMPER	1
03-35-05		Air horn actuation,Steer wheel & RH foot swtc	1
05-18-BE		18,000 lb ArvinMeritor front axle	1
06-12-BE		Michelin XZE 12R 22.5 16 PR "H" 9.00 F 15,800 lbs	1
06-50-10		Front Wheels, Polished aluminum, 9.00"	1
06-50-30		Front wheel bearings, Oil lubricated	1
06-50-35		Front shock absorbers Bilstein	1
06-50-45		Steering column & wheel, Tilt telescopic type	1
06-60-10		Front brakes 16.5" x 6" S-Cam w/auto slacks	1
07-24-BE		24,000 lb. Meritor RS-24-160	1
07-32-02		Top speed: 65 MPH, Single rear axle	1
07-35-10		Rear brakes 16.5 X 7" S cam single axle	1
07-36-10		WABCO ABS Brakes, Front & single rear	1
08-11-36		> Michelin XDN 11R 22.5 "H" 16PR 8.25 R 24,000 lbs	1
08-50-10		Polished aluminum rear wheels, 8.25" (4)	1
08-50-30		Rear wheel bearings, Oil lubricated	1
09-10-05		Rear suspension 57.5" x 3" vari-rate springs	1
11-10-05		Air brake system single axle / 4,136 total	1
11-20-10		Air Dryer, WABCO System Saver 1200	1
11-30-05		Manual drains - air brake system	1
11-40-05		Nylon air line tubing	1
11-40-21		Additional air reservoir air horns 1200 cu in	1
11-50-10		Engine Air compressor, 18.7 CFM, CUMMINS	1
12-10-BE		> Cummins ISC 330 hp electronic engine	1
12-22-10		Engine Warranty, Cummins 5 yr/100,000 miles	1
12-25-10		Fuel Filter - Cummins engine	1
12-30-10		> Jacobs Extarder, engine exhaust brake	1
12-50-18		Exhaust system	1
12-50-30		Air cleaner & air restriction indicator	1
13-10-05		Cooling system w/silicone radiator hoses	1
13-10-10		Engine fan, standard	1
13-20-05		Silicone Heater Hose	1
13-20-11		Coolant filter w/shut-off valve	1
14-10-02		Allison 3000 EVS 5-speed transmission	1

PART NO	S	DESCRIPTION	QTY
14-25-03		Transmission range selector, Push pad, Std	1
14-25-15		Mode button deprogrammed, 5th gear start-up	1
14-30-05		Drivelines, #1710 Heavy duty series	1
14-50-11		> Transmission Warranty, 3000 EVS (5) years	1
15-05-BE		Electrical system, 3 batteries ADV	1
15-10-05		Instrumentation, Standard	1
15-20-08		270 amp Leece Neville Alternator	1
15-30-02		> Kussmaul 1000 battery condition w/receptacle	1
16-05-08		Quad Headlights w/2 warning, 2 outer turns	1
16-05-20		Cab marker lamps-LED-cab face abv windshield	1
17-MF-04		Flat Floor MFD 10" raised roof cab	1
18-05-13		Full length cab doors, FLAT FLOOR, 10" RAISED ROOF	1
19-10-03		Engine tunnel, flat floor	1
19-40-15		Engine tunnel work light, one (1)	1
20-10-02		Driver -Seats Inc. 911 Univ REG.BACK N/SUSP	1
20-12-09		> Imperial 1200 covered seats	1
20-50-15		Officer-Seats Inc. 911 Universal REG.BACK ADV	1
21-50-15	S	Deleted for installation of cab command center cabinets	1
22-05-07		Interior paint gray Zolotone texture finish	1
22-10-05		Gray interior trim with gray floor mat	1
22-15-00		Front overhead heater	1
22-20-06		> Air conditioning, engine tunnel mount evaporator	1
23-05-25		Cab tilt actuation	1
23-20-10		Full wheel well liners	1
23-30-35		Cab side windows, FIXED (std)	1
24-10-05		Assist handles 18" stainless steel (4)	1
25-20-20		Exterior Mirrors, Remote,heated west coast	1
27-10-05	S	Cab Painting two-tone color exterior	1
28-10-05		Operators manual and parts list (1 set)	1
28-10-18		One (1) engine & transmission operation manual	1
28-20-05		Fire extinguisher	1
10-19-0100		< > FLUID LEVEL DATA - ELECTRONIC DISPLAY -- Downloaded into Vista display screen.	1
10-19-1000		< > "MUST BE SEATED AND BELTED" WARNING PLATE -- On cab dash visible to driver and crew	1
10-40-0000		< > SEAT MODULE - 2-MAN, BENCH & BACK REST -- Requires seat belts if used during transit. -- Bright aluminum tread plate storage base with flip up seat cushion and fixed back rest Upholstery Color: Gray Location: centered on rear wall of cab  ***Note to Harold/Jimmy: The front of the seat module base will hinge down to allow full access to bose storage when in the "open" position. This seat module will not be equipped with seat belts, which will prohibit any personnel from being seated during transit.***	1
10-50-0600	S <	CAB COMMAND CENTER, DESK & CABINETS BEHIND DRIVER -- Requires a minimum 10" raised roof. -- Refer to drawing D-03C-432 for cabinet layout.	1
10-99-0100		EXHAUST PIPE LOC.FRWRD OF RIGHT WHEELS	1
11-33-0000	<	STEP LIGHTS, FRONT CAB DOORS (PR) -- Recessed into side panel of left and right cab steps -- Automatically activated when left and right front cab doors are opened	1
11-33-0500	<	STEP LIGHTS, REAR CAB DOORS (PR) -- Recessed into side panel of left and right rear cab steps -- Automatically activated when left and right rear cab doors are opened -- Includes door jam switches	1
11-40-SPEC	X <	AIR HORN SWITCH - DIAMOND TREADPLATE RISER	1

PART NO	S	DESCRIPTION	QTY
		-- The officer's side air horn switch will be remounted on top of diamond treadplate riser to prevent accidental activation.	
11-42-1000	< >	AIR HORN MOUNTING - IN FRONT BUMPER Location(s): one (1) outside of frame rail, roadside (left) and curbside (right)	1
15-31-0000	>	FILLER PANEL, DP FOR EXTENDED BUMPER - CUSTOM CABS	1
16-10-0000	>	TOW HOOKS, REAR (PR) UNDER REAR STEP BUMPER	1
20-00-0000		***BODY & FRAME***	1
20-00-0700	< >	DROP/PINCH FRAME MODIFICATION - CUSTOM CABS -- OEM Rail location pinched inward to provide 40" comp't depths full height on all compartment forward of rear axle -- Upper Pinch Rails - 9"H x 2-1/2" wide x 1/4" thick frame steel -- Lower Drop Rails - 5"H x 3"W x 1/4" thick tubular steel -- All DOT and ABS wiring routed in protective loom on the inside left rail	1
20-02-0000	<	BODY CONSTRUCTION - HEAVY RESCUE -- 100% aluminum construction - 10 year structural warranty -- All compartments rated at a minimum of 2300 lbs load capacity each -- 1/8" smooth aluminum reinforced floors for all tall compartments. 3/16" smooth reinforced floor for wheelhouse compartment. -- All compartments with roll-up doors, painted to match body & cab with integral door tracks - compartment interior width equal to door pass-thru -- Bright aluminum tread plate roof welded around perimeter -- .125 smooth aluminum front and rear covers - welded -- Radius corner and roof rail extrusions - no blunt or formed edges	1
20-11-4700	S < >	BODY - DFC1073R - 10-COMP'T W/RECESSED ROOF #1,CS/RS - 48W x 73H x 40D #2,CS/RS - 48W x 73H x 40D #3,CS/RS - 52W x 48H x 90D #4,CS/RS - 27W x 48H x 90D #5,CS/RS - 40W x 73H x 40D	1
20-72-2000	<	FUEL FILLER W/HINGED ACCESS DOOR -- fuel filler hoses furnished by chassis manufacturer -- CPI - C10442	1
20-72-3000	<	DIESEL FUEL ONLY LABEL -- Engraved letters - metallic label next to fuel fill	1
20-81-0000	<	OVERALL HEIGHT PLATE - NFPA -- Approx. 6"W x 3"H - Red plate with white letters prominently displayed on center of cab dash -- WARNING - 10' 3" CLEARANCE (or actual height at time of delivery)	1
22-10-0000		STONE GUARDS, FRT & REAR - D/P CORNERS (4)	1
22-10-5000		MUD FLAPS, REAR (PR) BLACK RUBBER	1
22-25-2000		BUMPER, REAR STEP BRIGHT TREAD PLATE	1
22-25-9000	<	SIGN - "DANGER - DO NOT RIDE ON REAR STEP" -- Metallic engraved -- Affix over rear step bumper "DANGER - DO NOT RIDE OR STAND ON REAR BUMPER/STEP WHILE VEHICLE IS IN MOTION. DEATH OR SERIOUS INJURY MAY RESULT"	1
22-31-3000	< >	STEP, RECESSED - EA CPI POLISHED ALUMINUM Location(s): one (1) fore and aft of rear axle opening in wheelhousing skirt, roadside (left) and curbside (right)	4
22-33-1000		STEP, REAR WHEEL ALUMINUM STEP (PR)	1
22-40-0000		WHEEL CHOCKS - ZICO COLLAPSIBLE TYPE (EA)	2

PART NO	S	DESCRIPTION	QTY
22-40-0100	<	HOLDER FOR WHEEL BLOCK - ZICO SQCH-44 (EA) Location(s): one (1) fore and aft of rear axle opening, under roadside of the body	2
22-50-3000	< >	LICENSE FRAME W/LIGHT-SURFACE MNT-CPI C30004 Location: above curbside (right) DOT light cluster	1
22-80-SPEC	X <	RECEIVER - SIDE MOUNT FOR REMOVABLE SEAT (EA) -- There will be a receiver mounted under roadside (left) and curbside (right) of the body, ahead of the rear axle, for the use of a removable seat furnished by the fire department.	2
23-10-1000	<	UNISTRUT TRACK UP TO 82"H - (4) Location(s): - #1,RS- starting 2" above generator control panel to top of section - #2,RS- starting 2" off floor to top of section - #3,RS- starting 10" off floor to top of section - #4,RS- starting 2" off floor to top of section - #1,CS- starting 10" off floor to top of section between the aft wall and 2" vertical partition - #1,CS- starting 2" off floor to top of section between the forward wall and 2" vertical partition - #2,CS- starting 10" off floor to top of section - #3,CS- starting 10" off floor to top of section - #4,CS- starting 2" off floor to top of section - #5,CS- starting 2" off floor to top of section	9
23-11-2000	<	SHELF (EA) UP TO 52"W X 44"D -- heavy-duty .190 aluminum w/ 1-1/2" open-end flange on four sides Location(s)/Size(s): - #1,RS- (1) 46W x 30D- adj - #2,RS- (2) 46W x 36D- adj - #5,RS- (1) 40W x 36D- fixed 58" off the floor - #1,CS- (3) 20W x 36D- adj between the forward wall and 2" vertical partition - #1,CS- (1) 22W x 36D- adj between the forward wall and 2" vertical partition - #2,CS- (2) 46W x 36D- adj - #5,CS- (1) 38W x 36D- adj	11
23-11-3000	<	SHELF (EA) UP TO 52" X 88"D -- heavy-duty .190 aluminum w/ 1-1/2" open-end flange on four sides -- requires (2) sets of UniStrut Location(s)/Size(s): - #4,RS/CS- (3) 25W x 88D- adj	3
23-21-1000	< >	TRAY, SLIDE-OUT 600# - 47W x 40D or less -- Black powder-coating on slider rails -- heavy-duty .190 aluminum w/3" welded flange on four sides -- Yellow/Black safety stripe tape on each side of tray Location(s)/Size(s): - #1,CS- (1) 23W x 36D- on floor between the aft wall and 2" vertical partition - #2,CS- (1) 47W x 36D- on floor - #5,CS- (1) 39W x 36D- on floor	3
23-21-1200	< >	TRAY, SLIDE-OUT 600# - 47W x 40D or more -- Black powder-coating on slider rails -- heavy-duty .190 aluminum w/3" welded flange on four sides -- Yellow/Black safety stripe tape on each side of tray Location(s)/Size(s): - #3,RS- (1) 51W x 42D- on floor - #3,CS- (1) 51W x 42D- on floor	2
23-21-4800	< >	TRAY, SLIDE/TILT - 46W X 40D or more -- Black powder-coating on slider rails	2

PART NO	S	DESCRIPTION	QTY
		-- heavy-duty .190 aluminum w/3" welded flange on four sides -- Yellow/black safety stripe tape on each side of tray Location(s)/Size(s): - #3,RS- (1) 46W x 42D- adj - #3,CS- (1) 46W x 42D- adj	
23-90-SPAA	X <	ALUMINUM STORAGE CUBICLES - 12W X 36D X 12H -- (12) 12W x 36D x 12H cubicles mounted on adjustable shelf Location: #5,CS	12
24-30-1000	<	PARTITION, VERTICAL HD 2" FRAMED PANEL TYPE Location(s)/Size(s): - #1,CS- (1) 67H x 30D- offset 24" off aft wall - #5,RS- (1) 58H x 30D- offset 8.5" off of the aft wall	2
24-31-2000	< >	DIVIDER, ALUMINUM 3/16" - UP TO 52" X 48" Size: 52W x 42H Location: #3,RS/CS- dividing the compartments into 45" depth	1
25-42-0100	S < >	ROOF COMP'T, HINGED LID - UP TO 192L x 32W x 12H -- (2) equal size lids, overlapping in center -- Bulbed gasket around perimeter of lid -- Gas-filled hold-open devices on each lid -- Draw-type-lok latch - one each end of both lids -- Drain holes in each corner -- Raised 1" off roof top Location: - one (1) roadside (left) of apparatus roof, adjacent to rear end section (174L x 32W x 12H) - one (1) curbside (right) of apparatus roof, adjacent to the light tower head (144L x 26W x 12H)	2
25-45-5100	S < >	SCBA SLIDE-OUT RACK STORAGE OF UP TO 10 SCBA -- Yellow/Black safety stripe tape along leading edge, left & right sides Location: #5,RS- between forward wall and 2" vertical partition (five (5) brackets will be installed on fore and aft sides of the slide-out rack)	1
25-50-2100	< >	SCBA WALKAWAY BRACKET - FLAMEFIGHTER -- Flamefighter brand w/vinyl clad clips Brand/Size/PSI: MSA 4500 PSI/60 MIN (Stealth Carbon Composite) Location(s): #5,RS- SCBA slide-out rack	10
25-50-3000	< >	SCBA STORAGE TUBE - PVC W/RUBBER STOPS Location(s): #5,RS- (6) between aft wall and 2" vertical partition	6
25-50-5000	<	SCBA STORAGE BOX W/PVC TUBE INSERTS - DUAL -- (2) tubes in each box Location(s): #5,RS- (2) mounted on upper fixed shelf	2
27-20-1000	< >	LADDER, ROOF ACCESS - OSHA TYPE -- NOTE: If OSHA observation platform is not specified, install label #65726 on body at top rung that read "CAUTION - Roof is not a walking-working surface. Properly restrained cargo-storage area only" -- knurled vertical vertical minimum 1" pipe -- Grip-Strut steps -- floating center attachment -- 7" extension roll above roof Location: curbside (right) rear of body	1
28-00-2000	< >	AWNING, SIDE BODY 17 - 21 FT. LONG -- Center support bracket for stored position Color: Black/Gray	2

PART NO	S	DESCRIPTION	QTY
		Location(s): one (1) roadside (left) and curbside (right) of the body	
		***Note to Harold/Shop: The awnings are to be mounted at the top of the upper side roof rails with thwe warning and scene lights to be mounted below.***	
40-00-0000		***PAINT & GRAPHICS***	1
40-00-0100		PAINT BODY - PRIMARY COLOR	1
40-00-2000	<	TWO-TONE BODY - DF & COMMAND MODELS	1
		Upper Color: White Brand/Code: FLNA 4006	
		Lower Color: Red Brand/Code: FLNA 3052	
		Breakline: Refer to attached drawing for paint breakline.	
42-12-0000	<	TOUCH-UP PAINT, ONE QUART	1
		Color(s): (1) Red/(1) White	
43-20-3000	<	STRIPE, REFLECTIVE 6" PRICE PER FOOT REQS DWG	70
		-- Straight application only.	
		Location: Refer to attached drawing for striping location.	
		Color: Gold	
43-20-9100	<	STRIPE, REFLECTIVE 1" PRICE PER FOOT REQS DWG	140
		Color: White	
		Location: Refer to attached paint layout drawing for striping location.	
43-20-9500	<	STRIPE - REFLECTIVE - FRONT BUMPER	1
		-- 4" full width of bumper extending around curvature - break between bumper mounted equipment or holes	
		Color: White	
45-10-0500		LETTER REFLECTIVE - 3" (EA)	23
45-10-2000	S	LETTER REFLECTIVE - 6" (EA)	26
45-20-1300		OUTLINE/SHADOW FOR 3" LETTER - NON-REFL (EA)	23
45-20-2000	S	RH OUTLINE/LEFT DROP SHADOW FOR 6" LETTER - NON-REFL (EA)	26
45-26-1000	S <	MALTESE CROSS - VINYL UP TO 24" X 24" - EA GR	3
		Design Layout: Refer to customer supplied graphics in Sales file.	
		Location(s):	
		- one (1) 15" x 15" on each of the front cab doors	
		- one (1) 24" x 24" centered on the rear of the body between the lower treadplate and the paint break line	
49-00-0000		UNDERCOATING CAB, FRAME & BODY	1
50-00-0000		***12VDC ELECTRICAL OPTIONS***	1
50-00-0400	>	ELECTRICAL SYSTEM - V-MUX MULTIPLEX	1
50-05-0000	<	AMP DRAW REPORT - NFPA 1901, Section 9-15	1
		-- Placed in Owners Manual at time of delivery	
50-40-0100	>	CLEARANCE LIGHTS, LED & REFLECTORS	1
50-50-0000	<	STOP/TAIL/BACKUP/TURN LIGHT ASSY - WHELEN	1
		CAST3 surface mount polished alum hsgs (2) LAMPS - Left side:	
		-- 64HCBR - red brake	
		-- 64HCWR - white backup	
		-- 64HCTR - amber arrow turn	
		LAMPS - Right side:	
		-- 64HCBR - red brake	
		-- 64HCWR - white backup	
		-- 64HCUR - amber arrow turn	
50-50-4000	< >	STOP LIGHT, LED AUXILARY UPPER - 4" (PR)	1
		-- Trucklite 44226R (42 diode) with 40705 polished stainless steel trim rings	
50-51-9000	<	AUXILIARY LED TURN SIGNALS - AMBER, CENTER BODY	1

PART NO	S	DESCRIPTION	QTY
		Location: midway of total apparatus length	
51-10-2100	<	SCENE LIGHT - SIDE - WHELEN 810 - (EA) - SURFACE MNT -- Model #810CAOZR - 8-32 degree optics -- Side lights surface mounted on upper roof rails. Qty. Ea. Side: 3	6
		***Note to Harold/Shop: The awnings are to be mounted at the top of the upper side roof rails with the warning and scene lights to be mounted below.***	
51-10-2500	<	SCENE LIGHT - REAR, WHELEN 810 - (EA) - SURFACE MNT -- Model #810CAOZR - 8-32 degree optics -- Rear lights surface mounted on body panel	2
51-15-1000	>	REVERSE ACTIVATED REAR SCENE LIGHT(S)	1
51-50-1000	< >	COMPARTMENT LIGHTS (EA) - 7" HALOGEN -- Weldon 1010-9200-80 surface mount	10
51-51-5000	S < >	COMP'T LIGHTS - ROOF -- Weldon 8045-GH1 halogen surface mounted -- Activated automatically when lid is raised and ambient light is low -- Includes switch for "Door Open" Warning Circuit Location(s): one (1) per lid of roof compartment	4
51-51-6000	<	ROOF WORK ZONE LIGHTS - SIDE WALL MOUNTED -- Activated by underbody ground light circuit.	3
51-55-1000	< >	COMP'T OPEN WARNING & AUTO ACTIVATION -- Activation switch incorporated into the "Door Open" circuit.	1
51-56-0100		COMP'T OPEN WARNING LIGHT	1
51-60-1000	S < >	DOME LIGHTS 12V HALOGEN - (2) IN CEILING -- Weldon 8045-0300-80 halogen - surface mounted in ceiling. -- Manual activation switch adjacent to roadside (left) rear cab door Location: two (2) equally spaced above desk top	1
51-75-1000	<	GROUND LIGHTS (EA) UNDERBODY MOUNTED Activated By: respective scene light switches & reverse mode Location(s): -- (1) ea. forward of left & right rear wheel -- (1) ea. aft of left & right rear wheels -- (1) under rear step bumper	5
51-80-2000	<	SPOTLIGHT, HAND-HELD - NITEHAWK 100,000 CP -- NovaTech Lighting System - 800-937-3110 Location: hardwired into OEM dash console	1
52-50-0000	S < >	STREAMLIGHT SL45102 HAND LIGHTS -12VDC CHARGER -- NFPA Requirement -- 12V Chargers connected to chassis batteries aft of battery switch Location(s): - one (1) roadside (left) and curbside (right) of seat module base, adjacent to rear wall of the cab	2
53-00-0000	< >	LOWER ZONE WARNING LIGHT PKG #1 - HALOGEN Includes: -- (2) - 60F000RR- Red mounted in upper headlight bezels with 6EHDLTMK headlight mounts -- (6) 60F000RR & 6EFLANGE - red - (1) left & right side of extended front bumper	1

PART NO	S	DESCRIPTION	QTY
		(1) left & right front body rail	
		(1) left & right rear side body rail	
		-- (2) 810CAARR - red - lower rear body	
53-01-0000	< >	UPPER ZONE WHELEN PKG #1, C4007 W/HALOGEN FLSH Light Bar: C400700N - 72", 4-rotator Light Bar Lens Color(s): Red, Clear, Red, Clear, Red Light Bar Location: cab roof Upper Side Body Flashers: 810CAARR - Red Upper Rear Body Flashers: (2) 810CAARR - Amber	1
		***Note to Harold/Shop: The awnings are to be mounted at the top of the upper side roof rails with thwe warning and scene lights to be mounted below.***	
53-30-1000	< >	HEADLIGHT WIG-WAG FLASHERS -- Controlled through V-Mux multiplex circuit and switched through the "Blocking" mode.	1
55-22-1000	< >	SIREN - ELECTRONIC WHELEN - WS295HFS1 Location: OEM dash console adjacent to Vista display screen	1
55-30-1000		HORN/SIREN SWITCH	1
55-40-0000	< >	SPEAKER, SIREN - WHELEN SA122FMA (EA) FLUSH Location: roadside (left) of front bumper	1
57-30-7000	S < >	ANTENNA W/COAXIAL, INSTALL CUSTOMER SUPPLIED -- The fire department will furnish the following antennas for installation: (1) 800 mhz (1) 800 mhz cellular (2) low band (1) high band (1) 900 mhz Location(s): cab roof	6
59-00-1000	>	BACK-UP ALARM	1
60-00-0000		***240/120VAC ELECTRICAL OPTIONS***	1
60-00-0500		ELECTRICAL - 120/240V - STANDARDS REQUIREMENT	1
61-01-1100	< >	GENERATOR - 25KW PTO - ELECTRONIC ENGINE APP -- DA Swirled finish on face panel -- PTO engage light on cab console and control panel. -- HIGH TEMP ALARM metallic tag above alarm buzzer Location: #1,RS	1
61-60-2000	< >	BREAKER BOX, 24-PLACE 125 AMP, SINGLE PHASE -- Install yellow labels identifying each breaker Location: #1,RS- on face of generator control panel	1
62-75-0000	<	TRANSFER RELAY, AUTOMATIC - 30 AMP -- Limited to outlets on same circuit only -- Automatically transfers power from generator to shorepower Dedicated Outlets: - (2) duplex outlets under cab desk - (1) duplex in #1,RS for department furnished/installed refrigerator	1
63-00-1000	< >	OUTLET 120V DUPLEX EXTERIOR WEATHERPROOF 20A -- metallic tag reading 120VAC above outlet Location: #1,RS- on face of generator control panel	1
63-00-2000	<	OUTLET,120V SGL TWIST NEMA L5-20R (EA) W/GFI -- metallic tag reading 120VAC above outlet Location(s):	4

PART NO	S	DESCRIPTION	QTY
		- two (2) lower roadside (left) rear body for tripod flood lights - one (1) aft of rear axle opening in wheelhousing skirt on RS/CS	
63-10-1000	< >	OUTLET 120V DUPLEX INTERIOR W/GFI, 20A (EA) Location(s): - two (2) on rear of engine doghouse, under command desk - (1) #1,RS centered on rear wall above generator control panel for refrigerator	3
63-20-0100	<	OUTLET 240V 30 AMP (EA) TWIST-LOK -- metallic tag reading 240VAC above outlet Location: #1,RS- on face of generator control panel	1
64-00-2000	< >	CORD REEL, ELECTRIC HANNAY ECR1624-17-18 -- CORD REEL REWIND metallic tag next to rewind button -- Type of cord: 10/4 Yellow -- Connection: <Permanent> Location: #1,RS- adjacent to aft wall	1
64-50-2000	< >	POWER DISTRIBUTION BOX - EXTENDA-LITE - 240VAC -- Model EJB-PP - yellow powder coated finish -- Split 240VAC circuit into two separate 120VAC circuits -- (1) L5-20R/(1) duplex twist-lock receptacle on each circuit - total of (2) of each -- Inlet: <Permanent> -- Lighted face plates on each side of box -- Handle on top of box	1
64-51-1000	<	DISTRIBUTION BOX WALL MOUNTING BRACKET -- EXTENDA-LITE EJB-VMT - powder coated yellow Location: Ship Loose	1
65-21-1000	<	TRI-POD FLOOD-MAGNAFIRE - 650W-120V (EA) -- Havis-Shields MagnaFire 3000 -- Head: Model 36 - 25,200 lumens -- Telescoping Pole - Model 800 tri-pod -- Individual circuit breakers for each light to specified outlets -- Brushed stainless steel backing plate on body behind light head nested position (as applicable to location) Location(s): two (2) on roadside (left) rear of body	2
65-30-2200	< >	LIGHT TOWER - NIGHTSCAN W/(6) 900W MULTI-DIRECTIONAL -- Transmission lock-out when tower not nested -- Red warning light on generator panel and cab console indicating tower up -- TOWER UP metallic tag next to alert light on generator panel and console -- Left & right light head banks tilt in opposing directions or simultaneously Tower Location: forward portion of body roof, mounted transverse with lighthoods to curbside (right) Remote Control Location: #1,RS- on face of generator control panel	1
66-00-1000	S <	LIGHT, FLUORESCENT - 110V 48" INT. CEILING Location: centered in upper forward portion of 10" raised roof, above desk top	1
80-00-0000		***MISCELLANEOUS EQUIPMENT***	1
89-15-0200	< >	FIRE EXTINGUISHER - 20A-80B:C - NFPA REQ'D Location: Ship Loose (w/bracket)	1
89-15-1000	< >	FIRE EXTINGUISHER - 2-1/2 GAL PRESSURIZED WAT Location: Ship Loose (w/bracket)	1
89-99-9000	>	MANUAL, HACKNEY OWNERS W/SCHEMATICS	1
89-99-9500	<	DOT SAFETY KIT -- Place in cab at time of delivery for DOT compliance.	1

