

# Shop Order

# Hackney Emergency Vehicle

**Quote For:**  
 SHASTA COUNTY  
 1610 W. STREET, SUITE A  
 REDDING, CA 96001

**Ship To:**  
 SHASTA COUNTY FIRE DEPT.  
 CHIEF SCOTT HOLMQUIST  
 875 CYPRESS AVE.  
 REDDING, CA 96001  
 530-225-2403

**Dealer:**  
 PLACER FIRE EQUIPMENT  
 SACRAMENTO, CA

**Terms:**  
 NET ON DELIVERY

**Drawing #:** D-04C-244-A  
**Delivery Date:** 09/07/04  
**Customer PO #:** 04F09041  
**Customer #:** 002445  
**QPF #:** QPF2445

**Penalty:**  
 N/A

**Quote No:** 10RC1-0002

10/01/2004

Page 1

PART NO	S	DESCRIPTION	QTY	ID
		== 8-COMP'T REAR COMMAND W/REC ROOF - ==	1	HS
		<b>CAB AND CHASSIS</b>	1	HS
		<b>CHASSIS RELATED OPTIONS</b>	1	HS
10-19-0100	< >	FLUID LEVEL DATA - ELECTRONIC DISPLAY Downloaded into Vista display screen.	1	HS
10-19-1000	< >	"MUST BE SEATED AND BELTED" WARNING PLATE On cab dash visible to driver and crew	1	HS
10-99-0100	<	EXHAUST PIPE LOC.FRWRD OF RIGHT WHEELS STRAIGHT CUT FOR NEDERMAN EXHAUST	1	HS
11-16-1000	<	BATTERY CONDITIONER - KUSSMAUL AUTOCHARGE 1000 BOM #806311 -- 18 amp - Single battery system - will charge up to (3) batteries and hand-lights simultaneously -- Does not include shorepower LED DISPLAY LOC: NEXT TO SHOREPOWER CONDITIONER LOC: BEHIND DRIVER SEAT	1	HS
11-17-2000	S <	SHOREPOWER, AUTO-EJECT - KUSSMAUL 20 AMP BOM #806287 SUPER Model - sealed weatherproof box -- Model #091-55-20-120 -- 091-3RD red cover LOC OF INLET: OVER LEFT FRONT WHEEL	1	HS
12-00-1000		MUD FLAPS, FRT (PR) BLACK RUBBER	1	HS
12-11-9000	<	DIESEL FUEL ONLY LABEL -- Engraved letters - metallic label next to fuel fill	1	HS
16-10-0100	>	TOW LOOPS (PR) UNDER REAR STEP BUMPER	1	HS
		<b>BODY and FRAME OPTIONS</b>	1	HS
20-00-0700	S < >	DROP/PINCH FRAME MODIFICATION - CUSTOM CABS -- OEM Rail location pinched inward to provide 40" comp't depths full height on all	1	HS

PART NO	S	DESCRIPTION	QTY	ID
		compartment forward of rear axle -- Upper Pinch Rails - 9"H x 2-1/2" wide x 1/4" thick frame steel -- Lower Drop Rails - 5"H x 3"W x 1/4" thick tubular steel -- All DOT and ABS wiring routed in protective loom on the inside left rail		
20-03-0000	S <	<b>BODY CONSTRUCTION - REAR COMMAND/WORK CENTER</b> -- 100% aluminum construction - 10 year structural warranty -- All compartments rated at a minimum of 2300 lbs load capacity each -- 1/8" smooth aluminum reinforced floors for all tall compartments. 3/16" smooth reinforced floor for wheelhouse compartment. -- All compartments with roll-up doors, painted to match body & cab with integral door tracks - compartment interior width equal to door pass-thru -- Bright aluminum tread plate roof welded around perimeter -- .125 smooth aluminum front and rear covers - welded -- Radius corner and roof rail extrusions - no blunt or formed edges	1	HS
20-12-2000	S < >	<b>BODY - CR0882R - 8-COMP'T REAR COMMAND W/REC ROOF</b> #1,CS/RS - 40W x 82H x 40D #2,CS/RS - 40W x 82H x 40D #3,CS/RS - 40W x 82H x 40D #4,CS/RS - 60W x 57H x 90D	1	HS
		<b>BODY OPTIONS</b>	1	HS
20-69-0000	S <	<b>OVERALL HEIGHT PLATE - NFPA</b> Approx. 6"W x 3"H - Red plate with white letters prominently displayed on center of cab dash -- WARNING - _?_'_'_'_' CLEARANCE (or actual height at time of delivery)	1	HS
		<b>INTERIOR PERSONNEL COMP'T OPTIONS</b>	1	HS
21-10-1000	S < >	<b>CABINETS &amp; DESK - REAR COMMAND</b> -- (2) adjustable shelves in each cabinet -- Poly coating on natural oak edges -- White cabinet liner on interior of cabinets and drawers -- Aluminum cove moulding around edges of counter/desk -- Securing mechanism on drawers to prevent opening during transit	1	HS
21-19-0000	< >	<b>FUME HOOD W/VAPOR-PROOF LIGHT &amp; BLOWER</b> LOC: ROAD SIDE FORWARD WALL CORNER-SEE DRAWING	1	HS
21-20-7000	S < >	<b>CHAIR, SWIVEL DESK TYPE</b> -- Staples #451636-53/Global #8964 Securing Instructions: Each chair shall be secured to desktop with bungee straps.	2	HS
21-25-0100	S <	<b>MARKER BOARD, WHITE DRY-ERASE - 48Lx36H</b> LOC: ON REAR WALL OF COMMAND CENTER	1	HS
21-30-1500	< >	<b>FLOOR, COMMAND CENTER - CONGOLEUM COMMERCIAL</b> Seascape #50053 Smoke	1	HS
		<b>EXTERIOR BODY OPTIONS</b>	1	HS
22-01-1010	S < >	<b>DOOR, SIDE PERSONNEL ENTRANCE W/WINDOW</b> -- Hansen 18" grab rail on inner door panel at an angle LOC: CS OF REAR COMMAND CENTER	1	HS
22-05-0110	S <	<b>WINDOW - COMMAND CTR 24"H X 36"W TINTED (EA).</b> <<NOTE: Does not meet DOT/NFPA secondary escape criteria>> LOC: RS OF REAR COMMAND CENTER	1	HS
22-20-1000		<b>MUD FLAPS, REAR (PR) BLACK RUBBER</b>	1	HS
22-21-0000		<b>STONE GUARDS, FRT &amp; REAR - D/P CORNERS (4)</b>	1	HS
22-25-2000		<b>BUMPER, REAR STEP BRIGHT TREAD PLATE</b>	1	HS

PART NO	S	DESCRIPTION	QTY	ID
22-25-9000	<	SIGN - "DANGER - DO NOT RIDE ON REAR STEP" -- Metallic engraved -- Affix over rear step bumper "DANGER - DO NOT RIDE OR STAND ON REAR BUMPER/STEP WHILE VEHICLE IS IN MOTION. DEATH OR SERIOUS INJURY MAY RESULT"	1	HS
22-31-3000	S < >	STEP, RECESSED - EA CPI POLISHED ALUMINUM LOCS: fore left & right rear wheel openings	2	HS
22-33-1000		STEP, REAR WHEEL ALUMINUM STEP (PR)	1	HS
22-40-0000		WHEEL CHOCKS - ZICO COLLAPSIBLE TYPE (EA)	2	HS
22-40-0100	<	HOLDER FOR WHEEL BLOCK - ZICO SQCH-44 (EA) LOC: RS IN FRONT OF REAR WHEELS	2	HS
22-50-3000	S < >	LICENSE FRAME W/LIGHT-SURFACE MNT-CPI C30004 LOC: BEHIND LADDER CS STANDARD LOCATION	1	HS
<b>INTERIOR COMP'T OPTIONS</b>				
23-10-1000	S <	UNISTRUT SHELF/TRAY TRACK - Set of (4) LOCS:  RS #1 10" ABOVE GENERATOR PERMANENT SHELF RS #2 10" FROM FLOOR RS #3 10" FROM FLOOR RS #4 10" FROM FLOOR CS #1 10" FROM FLOOR CS #2 10" FROM FLOOR CS 34 10" FROM FLOOR	1 7	HS HS
23-11-2000	S <	SHELF (EA) up to 38W X 36D -- heavy-duty .160 aluminum w/ 1-1/2" open-end flange on four sides SIZE & LOC:  RS #1 (2) RS #2 (2) RS #3 (2) CS #1 (2) CS #2 (2)	10	HS
23-11-3010	S <	SHELF (EA) up to 72" X 88"D -- heavy-duty .160 aluminum w/ 1-1/2" open-end flange on four sides Requires (2) sets of UniStrut SIZE & LOC: CS/RS #4 TRANSVERSE	1	HS
23-21-1010	S < >	TRAY, SLIDE-OUT 600# - up to 52W x 38D -- Black powder-coating on slider rails -- heavy-duty .160 aluminum w/3" open-end flange on four sides -- Yellow/Black safety stripe tape on each side of tray SIZE & LOCS:  FLOOR RS #3 FLOOR CS #2	2	HS
23-21-3010	S < >	TRAY, TRANSVERSE SLIDE-OUT - up to 73W X 88D -- Black powder-coating on slider rails -- heavy-duty .160 aluminum w/3" open-end flange on four sides -- Yellow/black safety stripe tape on each side of tray. -- Up to 52" wide SIZE & LOC: CS/RS #4 FLOOR TRANSVERSE	1	HS
23-21-5020	S < >	TRAY, SLIDE/TILT - up to 52W X 40D	2	HS

PART NO	S	DESCRIPTION	QTY	ID
		-- Black powder-coating on slider rails -- heavy-duty .160 aluminum w/3" open-end flange on four sides -- Yellow/black safety stripe tape on each side of tray SIZE & LOCS:		
		RS #3 (1) CS #2 (1)		
25-40-1000	< >	STOKES/BACKBOARD TUNNEL- 1-STOKES; 2-BACKBOARD WHEELHSG LOC: ROOF FOR RS/CS ACCESS	1	HS
25-45-0000	< >	TOOL BOARD-SLIDE-OUT - VERTICAL - PLYWOOD PANEL -- Mounted on 400# SlideMaster bolted to floor. -- Upper section supported between two polypropylene gliders -- Surface sanded and coated with clear polyurethane -- Yellow/Black safety stripe tape along leading edge, left & right sides LOC: CS #3 RIGHT SIDE OF COMPARTMENT. SEE DRAWING	1	HS
25-45-5100	S < >	SCBA SLIDE-OUT RACK STORAGE OF UP TO 8 SCBA -- Yellow/Black safety stripe tape along leading edge, left & right sides LOC: CS #3 FAR LEFT SIDE OF COMPARTMENT-SEE DRAWING	1	HS
25-45-5410	S < >	SCBA WALKAWAY BRACKET - FLAMEFIGHTER Flamefighter brand w/vinyl clad clips BOTTLE PSI/SIZE/BRAND: LOC: SHIP LOOSE FOR CUSTOMER INSTALLATION	8	HS
25-50-3000	S < >	SCBA STORAGE TUBE - PVC W/RUBBER STOPS LOC: CS #3 ROOF FAR LEFT SIDE ABOVE SLIDEOUT SCBA RACK. SEE DRAWING	6	HS
25-50-6000	S < >	SCBA BOTTLE W/HSG STORAGE W/HINGED DOOR (EA) LOC: CS WHEELHOUSE BEHIND REAR WHEELS	2	HS
		<b>EXTERIOR OPTIONS</b>		
26-00-0010	< >	LADDER, ROOF ACCESS - OSHA TYPE -- NOTE: If OSHA observation platform is not specified, install label #65726 on body at top rung that read "CAUTION - Roof is not a walking-working surface. Properly restrained cargo-storage area only" -- knurled vertical vertical minimum 1" pipe -- Grip-Strut steps -- floating center attachment -- 7" extension roll above roof LOC: CS	1 1	HS HS
26-00-0200	S < >	ROOF COMP'T, HINGED LID - 192L x 26W x 12H -- (2) equal size lids, overlapping in center -- Bulbed gasket around perimeter of lid -- Gas-filled hold-open devices on each lid -- Draw-type-lok latch - one each end of both lids -- Drain holes in each corner -- Raised 1" off roof top -- See 51-51-50 or 51-51-51 for Comp't Light & "Comp't Open" warning LOC: CS/RS ALLOWING FOR ACCESS AROUND A/C CONDENSOR	2	HS
28-00-3500	S < >	AWNING, ELECTRIC CONTROLLED - UP TO 22 FT COLOR: Pewter  LOC: CS AND RS OF BODY  CONTROL BOX LOC: CS/RS REAR OF BODY ABOVE DIAMONDPLATE CLOSE	2	HS

PART NO	S	DESCRIPTION	QTY	ID
		TO EDGE AS POSSIBLE. SEE DRAWING		
		<b>PAINT OPTIONS</b>		
40-00-0100	<	PAINT BODY - PRIMARY COLOR	1	HS
		-- Clear urethane top coat - mirror finish (no "orange peel" effect)	1	HS
		COLOR: RED CODE/BRAND: MATCH SPARTAN CAB-SEE NEAL FOR		
		PAINT CODE GIVEN BY EDDIE SMITH 5/13/04		
40-00-2000	<	TWO-TONE BODY - DF & COMMAND MODELS	1	HS
		UPPER COLOR: WHITE CODE/BRAND: 4006 FLNA		
		LOWER COLOR: RED CODE/BRAND: SEE BODY		
		BREAK LINES: UPPER BODY PANEL ABOVE DRIP RAILS WHERE		
		SCENE/WARNING LIGHTS ARE		
42-12-0000	<	TOUCH-UP PAINT, ONE QUART	1	HS
		COLOR(S): RED		
42-99-0000		UNDERCOATING CAB, FRAME & BODY	1	HS
		<b>LETTERING and GRAPHICS</b>	1	HS
43-20-3000	<	STRIPE, REFLECTIVE 6" PRICE PER FOOT REQS DWG	72	HS
		Straight application only.		
		LOC: SHASTA TO PROVIDE ON APPROVAL DRAWING		
		COLOR: WHITE		
43-20-9500	<	STRIPE - REFLECTIVE - FRONT BUMPER	1	HS
		4" full width of bumper extending around curvature - break between bumper		
		mounted equipment or holes		
		COLOR: WHITE		
45-10-1000	S <	LETTER REFLECTIVE - 4" (EA)	24	HS
		SHASTA TO PROVIDE ON APPROVAL DRAWING		
45-10-2500	S <	LETTER REFLECTIVE - 8" (EA)	60	HS
		SHASTA TO PROVIDE ON APPROVAL DRAWING		
		<b>12VDC ELECTRICAL OPTIONS</b>		
50-00-0400	< >	ELECTRICAL SYSTEM - V-MUX MULTIPLEX	1	HS
		Vista Control Panel on flexible	1	HS
		-- Swivel pedestal mounted OR flush in console		
		-- Function switches next to LCD screen with switch functions displayed on LCD		
		for each switch		
		-- Sunlight visible LCD screen with:		
		-- Diagnostics screen		
		-- Automatic fault code display		
		-- Fluid level screen		
		-- Warranty notification screen		
		Multiplex wiring and power control modules		
		Load Manager		
		Engine automatic high idle		
50-05-0000	<	AMP DRAW REPORT - NFPA 1901, Section 9-15	1	HS
		Placed in Owners Manual at time of delivery		
		<b>DOT LIGHTING</b>		
50-40-0100	< >	CLEARANCE LIGHTS, LED & REFLECTORS	1	HS
		Kit #3293399	1	HS
50-50-0000	<	STOP/TAIL/BACKUP/TURN LIGHT ASSY - WHELEN	1	HS
		CAST3 surface mount polished alum hsgs (2) LAMPS - Left side:		
		-- 64HCBR - red brake		
		-- 64HCWR - white backup		

PART NO	S	DESCRIPTION	QTY	ID
		-- 64HCTR - amber arrow turn LAMPS - Right side: -- 64HCBR - red brake -- 64HCWR - white backup -- 64HCUR - amber arrow turn		
50-50-4000	< >	STOP LIGHT, LED AUXILARY UPPER - 4" (PR) Trucklite 44226R (42 diode) with 40705 polished stainless steel trim rings	1	HS
50-51-9000	<	AUXILIARY LED TURN SIGNALS - AMBER, CENTER BODY LOC: midway of total apparatus length	1	HS
50-55-0000	< >	TRAFFIC ADVISOR - LED THINLINE -- 38.5"L Controlled by single switch on primary LCD screen. When activated, second screen appears with following function selections: 1. Left directional 2. Right directional 3. Center out directional 4. Wig-wag pattern	1	HS
		<b>12VDC APPARATUS ILLUMINATION and OPTIONS</b>		
51-10-2100	<	SCENE LIGHT - SIDE - WHELEN 810 - (EA) - SURFACE MNT Model #810CAOZR - 8-32 degree optics -- Side lights mounted on polished aluminum pods on contour of roof rails -- Rear lights surface mounted on body panel QTY EA. SIDE:	4	HS
51-10-2500	<	SCENE LIGHT - REAR, WHELEN 810 - (EA) - SURFACE MNT Model #810CAOZR - 8-32 degree optics -- Side lights mounted on polished aluminum pods on contour of roof rails -- Rear lights surface mounted on body panel	2	HS
51-10-2501	X <	CAB SCENE LIGHTS WHELEN 810 MOUNT HIGH AS POSSIBLE BEHIND FRONT CAB DOORS. WIRE TO VISTA SCREEN SCENE LIGHT ACTUATION BUTTONS	2	
51-15-1000	>	REVERSE ACTIVATED REAR SCENE LIGHT(S)	1	HS
51-50-1000	< >	COMPARTMENT LIGHTS (EA) - 7" HALOGEN WELDON 1010-9200-80 surface mount	8	HS
51-51-5000	< >	COMP'T LIGHTS - ROOF WELDON 8045-GH1 halogen surface mounted -- Activated automatically when lid is raised and ambient light is low -- INCLUDES switch for "Door Open" Warning Circuit LOCS:	4	HS
51-51-6000	<	ROOF WORK ZONE LIGHTS - SIDE WALL MOUNTED -- Activated by underbody ground light circuit.	3	HS
51-55-1000	< >	COMP'T OPEN WARNING & AUTO ACTIVATION Activation switch incorporated into the "Door Open" circuit.	3	HS
51-56-0100	<	COMP'T OPEN WARNING LIGHT BOM #812355	1	HS
51-60-1000	< >	DOME LIGHTS 12V HALOGEN - (4) IN CEILING WELDON 8045-0300-80 halogen - surface mounted in ceiling. -- Automatic activation when door(s) are opened -- Manual activation when doors are closed -- Switch on panel next to entrance door	4	HS

PART NO	S	DESCRIPTION	QTY	ID
		LOC:		
51-75-1000	<	GROUND LIGHTS (EA) UNDERBODY MOUNTED ACTIVATED BY: TRANSMISSION IN NEUTRAL AND PARKING BRAKE APPLIED	6	HS
		LOCS:		
		-- (1) ea. forward of left & right rear wheel		
		-- (1) ea. aft of left & right rear wheels		
		-- (1) under rear step bumper		
		_ (1) under personnel door		
52-50-0000	S < >	STREAMLIGHT SL45102 HAND LIGHTS -12VDC CHARGER NFPA Requirement 12V Chargers connected to chassis batteries aft of battery switch (requires battery conditioner) LOC: IN CAB BELOW A/C FAING REAR LOWER PART OF ENGINE COVER	2	HS
		<b>NFPA 1901 WARNING LIGHTS</b>	1	HS
		<b>LIGHT BARS</b>	1	HS
54-01-1460	<	WHELEN CENTURION C4002000 60" LIGHT BAR LOC: CAB ROOF LENS: RED	1	HS
		<b>LOWER ZONE A - FRONT CAB WARNING LIGHTS</b>	1	HS
54-10-0550	<	WHELEN 580CAARR HALOGEN (ea) LOC: IN HEADLIGHT BEZEL OUTSIDE LENS: RED	2	HS
		RS LIGHT TO BE STEADY BURNING		
54-15-5000	< >	HEADLIGHT WIG-WAG FLASHERS Controlled through V-Mux multiplex circuit and switched through the "Blocking" mode. -- INOPERABLE ON HI-BEAM	1	HS
		<b>LOWER ZONE B/D - CAB INTERSECTION WARNING LIGHTS</b>	1	HS
54-20-0600	S <	WHELEN 580CAARR HALOGEN (ea) LOC: SIDE OF BUMPER EXTENSION LENS: RED	2	HS
		<b>LOWER ZONE B/D - LOWER SIDE BODY WARNING LIGHTS</b>	1	HS
54-21-0500	<	WHELEN 60F000RR HALOGEN (ea) LOC: FRONT/REAR RUBRAIL CS/RS LENS: RED	4	HS
		<b>LOWER ZONE C - REAR BODY WARNING LIGHTS</b>	1	HS
54-25-1020	<	WHELEN 810CAARR HALOGEN (ea) COLOR: red	2	HS
		LOC: BELOW TAIL LIGHTS		
		<b>UPPER ZONE B/D - SIDE BODY WARNING LIGHTS</b>	1	HS
54-30-0600	<	WHELEN 810CAARR HALOGEN (ea) LOC: CS/RS UPPER 2 PER SIDE STD. LOCATIONS LENS: RED	4	HS
54-30-9000		MOUNTING PODS - UPPER SIDE BODY LIGHT	4	HS
		<b>UPPER ZONE C - REAR BODY WARNING LIGHTS</b>	1	HS
54-31-0400	< >	WHELEN 810CAAAR HALOGEN (ea)	2	HS

PART NO	S	DESCRIPTION	QTY	ID
		LOC: UPPER REAR OF BODY CS/RS LENS: AMBER LEFT/RED RIGHT		
		<b>SIRENS and SPEAKERS</b>		
55-20-1000	<	SIREN - FEDERAL ELECTRONIC - PA300MSC LOC: MOUNT LS DASH CLOSE AS POSSIBLE FOR DRIVER USE	1 1	HS HS
55-30-1000		HORN/SIREN SWITCH	1	HS
55-40-2200	S < >	SPEAKER, SIREN - FEDERAL MS100 DYNAMAX -- with MSFMT-EF chromed trim bezel -- Flush mounted -- 2.6" deep (recommended when chain boxes or reels are installed in front bumper speaker locations) -- 5.8"H x 5.8"W LOC:	1	HS
55-40-2201	X	RELOCATE AIR HORN FOOT SWITCH RS TO LS FOR DRIVER USE	1	
		<b>12VDC MISCELLANEOUS OPTIONS</b>		
57-30-5000	S < >	ANTENNA COAXIAL W/PL259 CONNECTOR PL259 soldered on termination point. 6" pigtail only at antenna site.  (2) CAB TO DOGHOUSE CENTER  (2) PERSONNEL COMPARTMENT ROOF TO UNDER INTERIOR CABINETS ON FRONT WALL OF PERSONNEL COMPARTMENT	4	HS HS
58-50-1100	S < >	12VDC POWER STRIP - (6) TERMINALS - BOD"Y LOC: UNDERNEATH UPPER CABINETS ON FRONT WALL OF PERSONNEL COMPARTMENT	1	HS
58-51-0000	S <	RECEPTACLE, 12VDC IN CAB -- 30 amp circuit breaker protected. -- rubber cover over opening LOC: ON DASH RS NEAR OFFICER SEAT	1	HS
58-51-0100	S <	RECEPTACLE, 12VDC IN BODY -- 30 amp circuit breaker protected. -- rubber cover over opening LOC: ON FRONT WALL OF PERSONNEL COMPARTMENT BELOW UPPER CABINETS CENTERED ABOVE THE MIDDLE DRAWER	2	HS
59-00-1000	>	BACK-UP ALARM	1	HS
59-10-0000	<	CARBON MONOXIDE MONITOR LOC: NEXT TO PERSONNEL DOOR	1	HS
		<b>240/120VAC ELECTRICAL OPTIONS</b>		
60-00-0500		ELECTRICAL - 120/240V - STANDARDS REQUIREMENT	1 1	HS HS
		<b>GENERATOR and OPTIONS</b>		
61-01-1100	S < >	GENERATOR - 25KW PTO - ELECTRONIC ENGINE APP -- DA Swirled finish on face panel -- PTO engage light on cab console and control panel. -- HIGH TEMP ALARM metallic tag above alarm buzzer LOC: RS #1	1	HS
61-08-2000	<	UL DIELECTRIC VOLTAGE WITHSTAND TEST UL test results to be included in Owner's Manual -- Tested to NFPA 1901, Chapter 23.16.2	1	HS
61-60-2000	S < >	BREAKER BOX, 24-PLACE 100 AMP, SINGLE PHASE Install yellow labels identifying each breaker LOC: RS #1	1	HS

PART NO	S	DESCRIPTION	QTY	ID
<b>120/240VAC OUTLETS, REELS and OPTIONS</b>				
62-20-3000	S < >	SHOREPOWER INLET, 30 AMP W/COVER & FEMALE PL -- Metallic label "SHOREPOWER" on top of inlet INLET LOC: CENTER REAR OF BODY ABOVE REAR STEP	1	HS
62-75-0000	S <	TRANSFER RELAY, AUTOMATIC - 30 AMP -- Limited to outlets on same circuit only -- Automatically transfers power from generator to shorepower DEDICATED OUTLETS: A/C IN PERSONNEL COMPARTMENT, ALL 110V IN PERSONNEL COMPARTMENT, REFRIGERATOR, 110V INTERIOR BODY COMPARTMENT LIGHTS	1	HS
63-00-1000	S < >	OUTLET 120V DUPLEX EXTERIOR WEATHERPROOF 20A -- metallic tag reading 120VAC above outlet LOC: CS/RS BEHIND REAR WHEELS, (1) REAR OF BODY NEXT TO TWIST LOCK	3	HS
63-00-2000	S <	OUTLET, 120V SGL TWIST NEMA L5-20R (EA) W/GFI -- metallic tag reading 120VAC above outlet LOC: CS/RS AHEAD OF REAR WHEELS/(1) REAR OF BODY NEXT TO LS TELESCOPING LIGHT SO LIGHT CAN BE PRECONNECTED TO TWIST LOCK	3	HS
63-10-3000	S <	OUTLETS, 120V STRIP W/6 RECEPTACLES & SURGE LOC: CENTERED FRONT WALL OF PERSONNEL COMPARTMENT BELOW UPPER CABINETS FOR DESKTOP USE	1	HS
64-00-2000	S < >	CORD REEL, ELECTRIC HANNAY ECR1624-17-18 -- CORD REEL REWIND metallic tag next to rewind button -- Type of cord: 10/4 Yellow -- Connection: L14-30R LOC: CS/RS #1 ROOF-SEE DRAWING	2	HS
64-50-2000	S < >	POWER DISTRIBUTION BOX - 240VAC - PLUG-IN MODEL EJB-PP - yellow powder coated finish -- Split 240VAC circuit into two separate 120VAC circuits -- (2) L5-15R twist-lock receptacles on each circuit - total of 4 -- Inlet: L14-30R -- Lighted face plates on each side of box -- Handle on top of box  PIGTAIL CONNECTIONS FROM CORD REEL	2	HS
<b>120/240VAC FLOOD LIGHTS and OPTIONS</b>				
65-21-1000	S <	TRI-POD FLOOD-MAGNAFIRE - 650W-120V (EA) HAVIS-SHIELDS MagnaFire 3000 -- HEAD: Model 36 - 25,200 lumens -- TELESCOPING POLE - Model 800 tri-pod -- Individual circuit breakers for each light to specified outlets -- Brushed stainless steel backing plate on body behind light head nested position (as applicable to location) LOC: REAR OF BODY-SEE DRAWING	1 2	HS HS
65-22-4800	S <	FLOOD LIGHT - UPPER BODY - 900W MAGNAFIRE Havis-Shields KR1939 w/integral recessed housing and 10 degree angle -- Individual circuit breakers for left & right -- Separate activation switch next to generator installation LOC: CENTERED UPPER SIDE OF BODY-SEE DRAWINGS	2	HS
65-30-2200	S < >	LIGHT TOWER - NIGHTSCAN W/(6) 900W MULTI-DIRECTIONAL TOWER LOC: FRONT OF BODY REMOTE CONTROL LOC: ON GENERATOR CONTROL PANEL	1	HS

PART NO	S	DESCRIPTION	QTY	ID
		-- Transmission lock-out when tower not nested -- Red warning light on generator panel and cab console indicating tower up -- TOWER UP metallic tag next to alert light on generator panel and console -- Left & right light head banks tilt in opposing directions or simultaneously -- 12V Spotlight at base of tower pointing upward to illuminate area directly over deployment zone		
65-30-8000	<	STROBE LIGHT TOP OF MAST - WILL-BURT -- automatically activated when out of "nested" position LENS COLOR: GREEN	1	HS
<b>120/240VAC MISCELLANEOUS OPTIONS</b>				
66-00-1000	S <	LIGHT, FLUORESCENT - 110V 48" INT. CEILING LOC: OVER PERSONNEL COMPARTMENT DESK. INTERIOR COMPARTMENT DOORS LOWERED TO MISS LIGHT FIXTURE WHEN OPENED.	1	HS
66-00-3000	S < >	LIGHT, FLUORESCENT - 110V EXTERIOR COMP'T (EA NOTE: Not applicable in wheelhouse comp't when stokes/backboard/ladder storage is chosen. -- Plastic sleeve on each tube. Activated by single circuit breaker switch. LOC: CS/RS #1, #2, #3	6	HS
68-00-1000	S < >	AIR CONDITIONER, 120V ROOF MOUNTED RV TYPE -- 39W x 43L x 14H -- Coleman Mach 15 with 5600 BTU heater	1	HS
68-10-1000	< >	HEATER, 1500W 120V - FLUSH WALL MOUNT (EA) LOC: BACK WALL OF PERSONNEL COMPARTMENT	1	HS
69-10-2200	S <	REFRIGERATOR/FREEZER - 9.7 cu.ft. - 120V NOTE: suggested that unit be powered from 30-amp shorepower and generator through 62-75-00 automatic transfer relay  33-1/2"H x 18-5/8"W x 19-3/8"D  LOC: CAB COMMAND CENTER PER DRAWING	1	HS
<b>MISCELLANEOUS EQUIPMENT and SERVICES</b>				
89-99-9000	>	MANUAL, HACKNEY OWNERS W/SCHEMATICS	1	HS
89-99-9500	<	DOT SAFETY KIT Place in cab at time of delivery for DOT compliance. -- Includes: Triangle Marker set; (1) flashlight; (1) 2-1/2# BC extinguisher	1	HS